

E-Coat Satin

E-coat Satin is your coated paper for everyday printing, offering an excellent quality/price ratio.

Colorful illustrations, books, brochures, luxury magazines, book covers, catalogs.

E-Coat Satin

PARAMETER	STANDARD	UNIT												
BASIS WEIGHT	ISO 536	g/m ²	90	100	115	130	135	150	170	200	250	300	350	400
THICKNESS	ISO 534	µm	64	72	84	94	94	110	128	152	185	229	273	320
SPEC. VOLUME	ISO 534	cm ³ /g	0,71	0,72	0,73	0,73	0,73	0,73	0,75	0,75	0,74	0,76	0,78	0,80
CIE WHITENESS (D65/10°)	ISO 11475	%	121	121	117	117	117	117	117	117	121	121	121	121
BRIGHTNESS (illuminant D65/10°)	ISO 2470-2	%	95	95	95	95	95	95	95	95	97	97	97	97
GLOSS DIN 75° (MD)	ISO 8254-2	%	47	47	47	47	47	47	47	47	47	47	47	47
GLOSS TAPPI 75°	ISO 8254-1	%	62	62	68	68	68	68	68	68	66	66	66	66
ROUGHNESS PPS	ISO 8791-4	%	0,7	0,7	0,8	0,8	0,8	0,8	0,8	0,8	0,6	0,7	0,7	0,8
OPACITY	ISO 2471	%	90	92	93	94	94	95,5	96,5	97,5	98,5	99	99	99,5
RELATIVE HUMIDITY (23°C)	TAPPI 502	%	50	50	50	50	50	50	50	50	50	50	50	50
PH VALUE	ISO 6588	-	>7	>7	>7	>7	>7	>7	>7	>7	>7	>7	>7	>7

These values are to be considered only as indications and are subject to change according to trade tolerances in the quality specification

Issue date: November 2010

